

Platax XL - ø 376 x h 100 mm



Plafoniera compatta stagna idonea per applicazioni civili, commerciali, alberghiere ecc. dove sono richieste caratteristiche di protezione contro l'ingresso di polveri o liquidi.

Corpo e cornice in nylon rinforzato con fibre di vetro, guarnizione in silicone, viteria imperdibile. **Riflettore** in alluminio stampato. **Diffusore** in policarbonato opale antiurto ed autoestinguente. **Cablaggio** composto da alimentazione 230V 50Hz, cavi in PVC HT 105° non propagante la fiamma, morsetteria 2P+T in nylon; doppio isolamento per la versione incandescenza.

Platax è installabile sia per impianto sotto parete che esterno; l'ingresso cavo è predisposto per un serracavo di diametro 16 mm.

Compact waterproof fitting suitable for public areas, halls, hotels, passages etc. where dust and water protection is necessary.

Casing and frame: nylon reinforced fibreglass, silicon gasket, non-loosening screws. **Reflector:** Pressed aluminium.

Diffuser: Self-extinguishing opal shockproof polycarbonate.

Wiring: 230V 50Hz power supply, HT105° non-flammable cable, nylon **connector block**, double insulated on incandescent version. The cable entry is predisposed for a 16 mm **cable gland**.

230/240V - 50 Hz

IP55



PLATAX XL con lampada ad Incandescenza (max 100W) / with Incandescent Lamp (max 100W)

Colour	W	pcs	pcs pallets	dm ³	kg		S + L Incand.
B/W	1x100	006	72	16,70	1,40	E27	702650.0139
N/B	1x100	006	72	16,70	1,40	E27	702651.0139

PLATAX XL con lampada Fluorescente Compatta Non Integrata / with Fluorescent Compact Lamp Not Integrated

Colour	W	pcs	pcs pallets	dm ³	kg		CNL 2700K
B/W	2x18	006	72	16,70	2,15	G24d-2	702661.0139
Colour	W	pcs	pcs pallets	dm ³	kg		CNL 2700K
B/W	2x26	006	72	16,70	2,15	G24d-3	702666.0139

CORNICI PER PLATAX XL ø 360 mm / FRAMES FOR PLATAX XL ø 360 mm

CO4001.100 = VISIERA/VISOR NYLON BIANCO/WHITE

CO4002.100 = VISIERA/VISOR NYLON NERO/BLACK

