

LAMPADE A SCARICA NEL GAS: IODURI METALLICI

DISCHARGE GAS LAMPS: METAL HALIDE



Code	Type	W	A		lm	mm	pcs	pcs	RA	Operating
						Ø L		pallets		position

Lampade ioduri metallici ad alta resa cromatica

Tubolari con bruciatore ceramico attacco G12 UV STOP (WDL=3000K - NDL=4200K)

Ceramic metal halide lamps for superior colour control

Tubular Ceramic Metal Halide lamps G12 base UV STOP (WDL=3000K - NDL=4200K)



500835.0101	HLI-C-T 35W/WDL	35	0,50	G12	3400	14,5 88	12		80+	univ.	NEW
500836.0101	HLI-C-T 35W/NDL	35	0,50	G12	3200	14,5 88	12		85+	univ.	NEW
500837.0101	HLI-C-T 70W/WDL	70	0,98	G12	6200	19 88	12		80+	univ.	NEW
500838.0101	HLI-C-T 70W/NDL	70	0,98	G12	6300	19 88	12		90+	univ.	NEW
500839.0101	HLI-C-T 150W/WDL	150	1,85	G12	14000	19 98	12		80+	univ.	NEW
500840.0101	HLI-C-T 150W/NDL	150	1,85	G12	13000	19 98	12		90+	univ.	NEW

Tubolari con bruciatore ceramico con doppio attacco RX7s - UV STOP (WDL=3000K - NDL=4200K)

Tubular Ceramic Metal Halide lamps RX7s double base UV STOP (WDL=3000K - NDL=4200K)



500830.0101	HLI-C-T2 70W/WDL	70	0,98	RX7s	5800	21 117,6	12		80+	p45	NEW
500831.0101	HLI-C-T2 70W/NDL	70	0,98	RX7s	5800	21 117,6	12		90+	p45	NEW
500833.0101	HLI-C-T2 150W/WDL	150	1,80	RX7s	13500	27 135,4	12		80+	p45	NEW
500834.0101	HLI-C-T2 150W/NDL	150	1,80	RX7s	12000	27 135,4	12		90+	p45	NEW

Lampade ioduri metallici tubolari per cablaggio sodio/ioduri

Con reattore SODIO accenditore 3,5 - 4,5 kV. Temperatura colore 5900K

Metal halide tubular lamps for sodium wiring

With SODIUM lamp ballast ignitor 3.5-4.5KV. Colour temperature: 5900K



500730.0101	HLI-T 250W	250	3,00	E40	25000	46 257	12		90	p45	NEW
500740.0101	HLI-T 400W	400	4/4,4	E40	40000	62 285	12		95	p45	NEW

Lampade ioduri metallici tubolari per cablaggio mercurio/ioduri

Con reattore Mercurio/ioduri accenditore 0,7-1,0 KV o 3,5 - 4,5 KV Temperatura colore: 4000K - 4200K

Metal halide tubular lamps for sodium or mercury wiring

With Mercury/Halide lamp ballast ignitor 0.7-1.0 KV o 3.5 - 4.5 KV Colour temperature: 3800K - 4000K

500731.0101	HLI-TP 250W	250	2,15	E40	20000	46 257	12		65	h90	NEW
500741.0101	HLI-TP 400W	400	3,25/3,5	E40	37000	62 285	12		65	h90	NEW

Funzionamento con accenditore esterno / Operating with external ignitor

500745.0101	HLI-T 1000 W/D	1000	9,50	E40	80000	76 340	6		90	P60	
-------------	----------------	------	------	-----	-------	--------	---	--	----	-----	--

Con accenditore interno / Ignitor included

500757.0101	HLI-T 2000 W/D	2000	10,30	E40	180000	100 430	4		95	p60	
-------------	----------------	------	-------	-----	--------	---------	---	--	----	-----	--

