



LAMPADE A SCARICA NEL GAS: IODURI METALLICI DISCHARGE GAS LAMPS: METAL HALIDE

Code	Type	W	A		lm	mm Ø	L	pcs	pcs pallets	RA	Operating position
------	------	---	---	--	----	---------	---	-----	----------------	----	-----------------------

Lampade ioduri metallici tubolari per cablaggio mercurio. 4300K Metal halide tubular lamps for mercury wiring 4300K

500744.0101	HLI-T 1000 W/NDL	1000	8,20	E40	85000	66	382	4		65	P20
500756.0101	HLI-T 2000 W/NDL	2000	8,80	E40	210000	102	430	4		65	P20
Con accenditore interno / Ignitor included											
500754.0101	HLI-T 2000 N	2000	8,80	E40	200000	100	430	4		65	P60



IODURI METALLICI - METAL HALIDE

Code	Type	W	A		lm	mm Ø	L	pcs	pcs pallets	RA	Operating position
------	------	---	---	--	----	---------	---	-----	----------------	----	-----------------------

Ellissoidali con vetro opale (4300K / 4500K) / Ellipsoidal with opal bulb (4300K / 4500K)

500778.0101	HLI-E 100 W/NDL	100	1,1	E27	7300	54	141	20		89	univ.
500779.0101	HLI-E 150 W/NDL	150	1,8	E27	10500	54	139	20		89	univ.



Ellissoidali con vetro chiaro (4300K / 4500K) / Ellipsoidal with clear glass (4300K / 4500K)

500792.0101	HLI-E 70 W/NDL	70	1	E27	5200	54	141	20		89	univ.
500793.0101	HLI-E 100 W/NDL	100	1,1	E27	7800	54	141	20		89	univ.
500794.0101	HLI-E 150 W/NDL	150	1,8	E27	11400	54	139	20		89	univ.

Code	Type	W	A		lm	mm Ø	L	pcs	pcs pallets	RA	Operating position
------	------	---	---	--	----	---------	---	-----	----------------	----	-----------------------

Lampade ioduri metallici con bulbo ellissoidale opalizzato per cablaggio sodio/ioduri Con reattore SODIO accenditore 3,5-4,5 KV. Temperatura colore 5200K - 5600K Metal halide lights with opalised ellipsoidal bulb for sodium/halide wiring With SODIUM reactor starter 3.5-4.5KV. Colour temperature 5200K-5600K

500780.0101	HLI-E 250W	250	3,00	E40	25500	90	215	12	576	90	univ.
500790.0101	HLI-E 400W	400	4/4,4	E40	42500	120	290	12		93	univ.



Lampade ioduri metallici con bulbo ellissoidale opalizzato per cablaggio mercurio/ioduri Con reattore MERCURIO/IODURI accenditore 0,7 - 1,0 KV o 3,5-4,5 KV. Temperatura colore: 3800K - 4000K Metal halide lights with opalised ellipsoidal bulb for mercury/halide wiring With MERCURY/HALIDE reactor starter 0.7-1.0KV or 3.5-4.5KV. Colour temperature: 3800K-4000K

500726.0101	HLI-EP 250W	250	2,15	E40	18000	90	215	12	576	65	h15
500728.0101	HLI-EP 400W	400	3,25/3,5	E40	32500	120	290	12		65	h15

Esempi di posizioni di funzionamento per lampade a scarica.
Example of operating position for discharge lamp.

